




Dati riferiti a travi con tensione normale ammissibile pari a 2400 kg/cmq

TRAVE SEMPLICEMENTE APPOGGIATA AGLI ESTREMI



N.B.: Ogni carico tabellato rappresenta esclusivamente il valore utile per la flessione

IPE.								
	11,50	12,00	12,50	13,00	13,50	14,00	14,50	15,00
80	265	248	232	217	203	190	178	166
100	478	450	424	400	377	356	335	316
120	765	723	684	648	613	581	551	522
140	1142	1082	1026	974	925	880	837	799
160	1638	1554	1477	1404	1337	1274	1214	1158
180	2221	2110	2008	1912	1823	1739	1661	1587
200	2981	2835	2700	2574	2457	2347	2244	2147
220	3906	3718	3543	3381	3230	3089	2957	2833
240	4953	4708	4480	4269	4072	3888	3715	3552
270	6747	6431	6138	5867	5614	5378	5157	4950
300	8814	8406	8028	7678	7352	7048	6764	6497
330	11339	10819	10338	9892	9478	9091	8729	8390
360	14436	13779	13172	12609	12086	11598	11142	10715
400	18605	17764	16989	16270	15603	14980	14399	13854
450	24151	23069	22070	21145	20286	19485	18737	18036
500	31180	29792	28511	27326	26224	25199	24241	23344
550	39518	37768	36153	34659	33271	31979	30772	29642
600	49853	47656	45630	43756	42015	40395	38882	37466